

Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 201 Revison:

Product type: SC50b

<u>Intended use:</u>: To be used in walls and partitions, as an ancillar components for masonry

(BSEN 1993-1-3 Structural Class III, intended to be used as a element that

only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics	Performance
Load Bearing Capacity (E _k , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	146.0
Mass per unit area (kg/m²)	NPD
Mass (kg/m)	13.6
Load Ratio	1:1 - 1:5

be he	EN
tion for ancillary components	
2 : 2012, Specification for a	: Lintels
EN 845 - 2: 2012,	masonary - Part 2:

	Clear Opening span (mm)	SWL UDL (kN)
	600	40
	750	40
	900	40
	1050	40
	1200	38
	1350	35
	1500	32
	1650	29
	1800	27
	1950	25
l	2100	23
l	2250	22
l	2400	21
l	2550	19
l	2700	18
l	2850	18
l		
l		
l		
l		
l		
l		
l		
l		
I		
I		
	-	-

TableA1:

Load bearing capacity

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)