



Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 202

Revision:

Product type: SC50c

Intended use: : To be used in walls and partitions, as an ancillary components for masonry
(BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer:

Harvey Steel Lintels
Commerce way, Whitehall Industrial Estate
Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering,
Research and Environmental Applications (CEREA)
Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics	Performance
Load Bearing Capacity (E _k , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	212.0
Mass per unit area (kg/m ²)	NPD
Mass (kg/m)	17.3
Load Ratio	1:1 - 1:5

hEN

EN 845 - 2 : 2012, Specification for ancillary components for masonry - Part 2: Lintels

TableA1:
Load bearing capacity

Clear Opening span (mm)	SWL UDL (kN)
600	50
750	50
900	50
1050	50
1200	50
1350	50
1500	50
1650	50
1800	50
1950	50
2100	47
2250	44
2400	42
2550	39
2700	37
2850	36
3000	34
3150	32
3300	31
3450	30
3600	28
3750	27
3900	26
4050	25
4200	24
4350	23
4500	21

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)