

Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 309 Revison:

Product type: SC125a

<u>Intended use:</u>: To be used in walls and partitions, as an ancillar components for masonry

(BSEN 1993-1-3 Structural Class III, intended to be used as a element that

only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics	Performance
Load Bearing Capacity (E _k , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	150.0
Mass per unit area (kg/m²)	NPD
Mass (kg/m)	18.6
Load Ratio	1:1 - 1:5

hE	N
_	
2 : 2012, Specification for ancillary components for	
ı for ancillary	
2 : 2012, Specificatior	Lintels
2:2012,	y - Part 2:
EN 845 - 2	masonary

Clear Opening	Clear Opening SWL UDL			
span (mm)	(kN)			
600	34			
750	34			
900	34			
1050	34			
1200	34			
1350	34			
1500	34			
1650	34			
1800	31			
1950	29			
2100	27			
2250	25			
2400	24			
2550	22			

TableA1:

Load bearing capacity

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)