



Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 341

Revision:

Product type: HC150

Intended use: To be used in walls and partitions, as an ancillary components for masonry
(BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer:

Harvey Steel Lintels
Commerce way, Whitehall Industrial Estate
Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering,
Research and Environmental Applications (CEREA)
Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics	Performance
Load Bearing Capacity (E _k , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)
Water Absorption	Zero
Water Vapour Permeability	Not Applicable
Thermal Resistance	Steel 64 W / m.k
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A
Durability (against corrosion)	Coating L14
Durability (against freeze/thaw)	Resistant
Dangerous Substance	None
Minimum Bearing Length (mm)	150 mm

Nominal Height (mm)	232.0
Mass per unit area (kg/m ²)	NPD
Mass (kg/m)	37.3
Load Ratio	1:1 - 1:19

hEN

EN 845 - 2 : 2012, Specification for ancillary components for masonry - Part 2: Lintels

TableA1: Load bearing capacity	
Clear Opening span (mm)	SWL UDL (kN)
600	80
750	80
900	80
1050	80
1200	80
1350	80
1500	80
1650	80
1800	80
1950	80
2100	80
2250	80
2400	80
2550	80
2700	80
2850	80
3000	80
3150	80
3300	80
3450	76
3600	73
3750	70
3900	68
4050	65
4200	61
4350	57
4500	53

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)