

Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 368 Revison:

Product type: BE 100-150

<u>Intended use:</u> : To be used in walls and partitions, as an ancillar components for masonry

(BSEN 1993-1-3 Structural Class III, intended to be used as a element that

only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is coverd by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.

The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3

Declared Performance:

Essential Characteristics Performance Load Bearing Capacity (Ek, in kN) Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL) Deflection Under Load Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1; 2005 NA) Water Absorption Zero Water Vapour Permeability Not Applicable Steel 64 W / m.k Thermal Resistance NPD (Contact Harvey steel for project specific details) document A Resistance to Fire Durability (against corrosion) Coating L14 Durability (against freeze/thaw) Resistant Dangerous Substance None Minimum Bearing Length (mm) 150 mm

Nominal Height (mm)	143.0
Mass per unit area (kg/m²)	NPD
Mass (kg/m)	17.4
Load Ratio	-

EN 845 - 2 : 2012, Specification for ancillary components for an amasonary - Part 2: Lintels

Clear Opening span (mm)	SWL UDL (kN)
600	55
750	55
900	55
1050	55
1200	55
1350	55
1500	55
1650	55
1800	55
1950	55
2100	55
2250	47
2400	41
2550	36
2700	31
2850	28
3000	24
3150	21
3300	19
3450	17
3600	15

TableA1:

Load bearing capacity

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

(Place and date of issue)

David Harvey (Managing director)

(Signature)