

## **Declaration of Performance**

EU Regulation No 305/2011, Annex III

	DOP Number: Product type: Intended use: : dustrial Estate	372 BE 140-150 To be used in walls and partitions, as an ancillar co (BSEN 1993-1-3 Structural Class III, intended to be only transfers loads to the structure)	•	element that	
Colchester, Essex CO2 8HH				TableA1: Load bearing capacity	
<u>The Notified Testing Laboratory:</u> University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL				Clear Opening span (mm)	SWL UDL (KN)
				600	60
Assessment and Verification of Constancy of Performance: System 3 <u>This DOP is coverd by following harmonised standard:</u> Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 - fulfil the conditions for CE Marking in accordance with annex ZA of EN 845-2: 2003.				750	60
				900	60
				1050	60
				1200	60
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3			d ZA.3	1350	60
				1500	60
				1650	60
Declared Performance:				1800	55
Essential Characteristics		Performance	hEN	1950	50
Load Bearing Capacity (E <sub>k</sub> , in kN)		Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)		2100	50
Deflection Under Load	Loss than off	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)	for	2250	45
			nts	2400	40
	-		one	2550	35
Water Absorption	Zero		dmo	2700	30
Water Vapour Permeability	Not Applicabl		L C	2850	30
Thermal Resistance	Steel 64 W / I		cilla		<b> </b>
Resistance to Fire		t Harvey steel for project specific details) document A	Specification for ancillary components for Lintels		
Durability (against corrosion)	Coating L14		on fo		
Durability (against freeze/thaw)	Resistant		catic		
Dangerous Substance	None		Specific Lintels		
Minimum Bearing Length (mm)	150 mm		Sp6		
			2012, Part 2:		
					1
Nominal Height (mm)		143.0			
		143.0 NPD			
Nominal Height (mm) Mass per unit area (kg/m <sup>2</sup> ) Mass (kg/m)					

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.07.2013

David Harvey (Managing director) T 1

(Place and date of issue)

(Signature)