

## **Declaration of Performance**

EU Regulation No 305/2011, Annex III

 DOP Number:
 259

 Product type:
 SC80EEa

 Intended use:
 To be use

<u>Revison: a</u>

TableA1:

Clear Opening

600

750

900

1050

1200

1350

1500

1650

1800

1950

2100

2250

span (mm)

Load bearing capacity

SWL UDL

30

30

30

30

27

25

23

21

19

18

17

16

(kN)

To be used in walls and partitions, as an ancillar components for masonry (BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

## This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 845-2: 2003. European Harmonised Standard EN 1090-1: 2009+A1:2011 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 1090-1: 2009 The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 of the above standards. Factory Production Control Certificate GB16/871495 refers

Declared Performance:

Essential Characteristics	Performance	hEN
Load Bearing Capacity $(E_k, in kN)$	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)	
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)	Specification for ancillary components for Lintels
Water Absorption	Zero	odu
Water Vapour Permeability	Not Applicable	cor
Thermal Resistance	Steel 64 W / m.k	llary
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A	anci
Durability (against corrosion)	Coating L14	for
Durability (against freeze/thaw)	Resistant	atior
Dangerous Substance	None	cific els
Minimum Bearing Length (mm)	150 mm	Specifi Lintels
		2012, Part 2:
Nominal Height (mm)	129.0	: 201 Part
Mass per unit area (kg/m <sup>2</sup> )	NPD	ary -
Mass (kg/m)	23.8	845 - 8
Load Ratio	1:1 - 1:5	EN mas

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.01.2025

(Place and date of issue)

Michael Polley (General Manager)

Delley