

## **Declaration of Performance**

EU Regulation No 305/2011, Annex III

 DOP Number:
 286

 Product type:
 EAL6 90EE

 Intended use:
 To be used

<u>Revison: a</u>

TableA1:

Clear Opening

600

900

1200

1500

1800

2100

2400

2700

3000

3300

3600

3900

4200

4500

4800

5100

span (mm)

Load bearing capacity

SWL UDL

190

190

190

190

190

190

190

190

190

173

159

147

137

122

107

95

(kN)

To be used in walls and partitions, as an ancillar components for masonry (BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer: Harvey Steel Lintels Commerce way, Whitehall Industrial Estate Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering, Research and Environmental Applications (CEREA) Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 845-2: 2003. European Harmonised Standard EN 1090-1: 2009+A1:2011 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 1090-1: 2009 The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 of the above standards. Factory Production Control Certificate GB16/871495 refers

**Declared Performance:** 

Essential Characteristics	Performance	hEN
Load Bearing Capacity ( $E_k$ , in kN)	Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)	
Deflection Under Load	Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA)	Specification for ancillary components for Lintels
Water Absorption	Zero	Iodu
Water Vapour Permeability	Not Applicable	cor
Thermal Resistance	Steel 64 W / m.k	llary
Resistance to Fire	NPD (Contact Harvey steel for project specific details) document A	anci
Durability (against corrosion)	Coating L14	for
Durability (against freeze/thaw)	Resistant	atior
Dangerous Substance	None	cific els
Minimum Bearing Length (mm)	150 mm	Specific Lintels
		: 2012, Part 2:
Nominal Height (mm)	238.0	
Mass per unit area (kg/m <sup>2</sup> )	NPD	ary -
Mass (kg/m)	68.1	EN 845 - 2 masonary
Load Ratio	1:1 - 1:19	EN ma:

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Harvey Steel 01.01.2025

(Place and date of issue)

Michael Polley (General Manager)

Dellay