



## Declaration of Performance

EU Regulation No 305/2011, Annex III

DOP Number: 313

Revision: a

Product type: HC125

Intended use: To be used in walls and partitions, as an ancillary components for masonry  
(BSEN 1993-1-3 Structural Class III, intended to be used as a element that only transfers loads to the structure)

Manufacturer:

Harvey Steel Lintels  
Commerce way, Whitehall Industrial Estate  
Colchester, Essex CO2 8HH

The Notified Testing Laboratory:

University of Glamorgan Commercial Services Centre for Engineering,  
Research and Environmental Applications (CEREA)  
Llantwit Road, Treforest Pontypridd, CF37 1DL

Assessment and Verification of Constancy of Performance: System 3

This DOP is covered by following harmonised standard:

Manufactured according to the requirements of the European Harmonised Standard EN 845-2: 2003 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 845-2: 2003.  
European Harmonised Standard EN 1090-1 :2009+A1:2011 and fulfil the conditions for UKAS Marking in accordance with annex ZA of EN 1090-1:2009  
The conformity assessment was executed in accordance with the method stated in tables ZA.2 and ZA.3 of the above standards. Factory Production Control Certificate GB16/871495 refers

Declared Performance:

| Essential Characteristics              | Performance   |
|--|---|
| Load Bearing Capacity ( $E_k$ , in kN) | Given in TableA1 as safe working loads (SWL) under uniform distributed loading (UDL)                    |
| Deflection Under Load                  | Less than effective span/325 as safe working load in service limit state (EN 1990: 2002 + A1 ; 2005 NA) |
| Water Absorption                       | Zero  |
| Water Vapour Permeability              | Not Applicable  |
| Thermal Resistance                     | Steel 64 W / m.k  |
| Resistance to Fire                     | NPD (Contact Harvey steel for project specific details) document A                                      |
| Durability (against corrosion)         | Coating L14   |
| Durability (against freeze/thaw)       | Resistant   |
| Dangerous Substance                    | None  |
| Minimum Bearing Length (mm)            | 150 mm  |

|  |            |
|--|------------|
| Nominal Height (mm)                    | 232.0      |
| Mass per unit area ( $\text{kg/m}^2$ ) | NPD        |
| Mass ( $\text{kg/m}$ )                 | 37.2       |
| Load Ratio                             | 1:1 - 1:19 |

**hEN**

EN 845 - 2 : 2012, Specification for ancillary components for masonry - Part 2: Lintels

| TableA1:<br>Load bearing capacity |              |
|-----------------------------------|--------------|
| Clear Opening span (mm)           | SWL UDL (kN) |
| 600                               | 80           |
| 750                               | 80           |
| 900                               | 80           |
| 1050                              | 80           |
| 1200                              | 80           |
| 1350                              | 80           |
| 1500                              | 80           |
| 1650                              | 80           |
| 1800                              | 80           |
| 1950                              | 80           |
| 2100                              | 80           |
| 2250                              | 80           |
| 2400                              | 80           |
| 2550                              | 80           |
| 2700                              | 80           |
| 2850                              | 80           |
| 3000                              | 80           |
| 3150                              | 80           |
| 3300                              | 80           |
| 3450                              | 78           |
| 3600                              | 75           |
| 3750                              | 72           |
| 3900                              | 69           |
| 4050                              | 66           |
| 4200                              | 62           |
| 4350                              | 58           |
| 4500                              | 54           |

Note:

Issued under the sole responsibility of Harvey steel Lintels

Signed on behalf of the manufacturer by :

Michael Polley (General Manager)

Harvey Steel 01.01.2025

(Place and date of issue)